## NSN 5935-01-380-2296

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-380-2296

Body Style:
Straight type
Overall Length:
2.350 inches
Overall Height:
0.350 inches
Overall Width:
0.250 inches
Environmental Protection:
Fungus resistant and corrosion resistant and vibration resistant and corrosion resistant and heat resistant and cold resistant and humidity
resistant and shock resistant
Unthreaded Mounting Hole Diameter:
0.120 inches
Distance Between Mounting Facility Centers:
2.100 inches
Mating End Quantity:
1
Contact Position Arrangement Style:
2 rows of contacts non-inserted board single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Polarization Method:
Guide pin/socket
Connector Locking Method:
Friction
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping
Insert Material:
Plastic diallyl phthalate single mating end
Contact Surface Treatment Specification:
Mil-g-45204 military specification single treatment response single mating end single contact grouping
Terminal Type:
Solder well single mating end single contact grouping

Included Contact Quantity:

30 single mating end single contact grouping

Unable to decode and unable to decode

**Included Contact Type:** 

**Unable To Decode:** 

Round pin single mating end single contact grouping

## NSN 5935-01-380-2296

Electrical Receptacle Connector - Page 2 of 2



Precious Material And Location:
Contact surfaces gold
<b>Precious Material And Weight:</b>
0.030 gold grains, troy
Precious Material:
Gold
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0

Mil-std (military Standard):

Mil-g-45204 spec.