

View Online at <https://aerobasegroup.com/nsn/5935-01-380-2312>

Thread Direction:

Right-hand

Body Style:

Straight shape, external coupling

Overall Length:

1.344 inches

Overall Height:

2.330 inches

Overall Width:

2.330 inches

Environmental Protection:

Moisture proof and salt water resistant and vibration proof and corrosion resistant and dust resistant and fuel resistant and fungus resistant and humidity resistant and oil resistant and shock resistant and thermal shock resistant and vibration resistant

Unthreaded Mounting Hole Diameter:

Between 0.142 inches and 0.152 inches

Center To Center Distance Between Mounting Facilities Parallel To Height:

2.000 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

2.000 inches

Distance From Mounting Shoulder To Front Face:

0.809 inches

Threaded Device Type:

Back shell

Mating End Quantity:

1

Polarization Method:

Keyway or multiple keyway

Insert Position In Deg:

0.0 and 110.0 and 250.0

Shell Type:

Solid

Connector Locking Method:

Detent

Thread Size:

44.0 millimeters

Insert Material:

Plastic single mating end

Shell Material:

Aluminum alloy

Shell Surface Treatment:

Cadmium and nickel

Shell Surface Treatment Specification:

Qq-p-416, ty ii, cl 3 federal specification single treatment response

Shell Material Specification:

Qq-a-225/8 federal specification 1st material response or qq-a-225/6, 6061-t6 or 2024-t4 federal specification 2nd material response

Thread Tolerance Class:

6g external

Thread Series Designator:

Iso m

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0