

View Online at <https://aerobasegroup.com/nsn/5935-01-380-3130>

Body Style:

Straight shape, external coupling

Overall Length:

0.765 inches

Overall Height:

0.625 inches

Overall Width:

0.260 inches

Environmental Protection:

Thermal shock resistant and moisture resistant and salt water resistant and vibration resistant and shock resistant

Unthreaded Mounting Hole Diameter:

0.103 inches

Distance Between Mounting Facility Centers:

0.481 inches

Distance From Mounting Shoulder To Front Face:

0.205 inches

Mating End Quantity:

1

Contact Position Arrangement Style:

Nonstd single mating end

Contact Removability:

Nonremovable single mating end single contact grouping

Contact Maximum Frequency Rating:

22.0 gigahertz single mating end single contact grouping

Shell Type:

Solid

Connector Locking Method:

Push-pull

Radio Frequency Type Contact Characteristic Impedance In Ohms:

50.0 single mating end single contact grouping

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping and nickel single mating end single contact grouping

Insert Material:

Plastic polytetrafluoroethylene single mating end

Terminal Type:

Crimp single mating end single contact grouping

Shell Material:

Stainless steel

Shell Surface Treatment:

Gold

Included Contact Quantity:

1 single mating end single contact grouping

Included Contact Type:

Round pin single mating end single contact grouping

Precious Material And Location:

Contact surface gold

Precious Material And Weight:

0.001 gold grains, troy

Precious Material:

Gold

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0