Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-380-5984

# Body Style:

Right angle type

## **Overall Length:**

1.800 inches

# **Overall Height:**

0.934 inches

#### **Body Width:**

Between 0.375 inches and 0.395 inches

#### **Body Height:**

0.330 inches

#### **Environmental Protection:**

Corrosion resistant and shock resistant and humidity resistant and thermal shock resistant and vibration resistant

#### **Unthreaded Mounting Hole Diameter:**

0.093 inches

#### **Distance Between Mounting Facility Centers:**

# 1.600 inches

Mating End Quantity:

2

## **Contact Position Arrangement Style:**

3 rows of contacts non-inserted board single mating end

#### Contact Removability:

Nonremovable single mating end single contact grouping

#### Contact Maximum Current Rating In Amps:

3.0 single mating end single contact grouping

## Contact Maximum Ac Voltage Rating In Volts:

1000.0 single mating end single contact grouping

#### **Polarization Method:**

Guide pin/socket

#### Shell Type:

Solid

#### **Connector Locking Method:**

Friction

#### **Operating Tempurature Rating:**

Between -55.0 degrees celsius and 105.0 degrees celsius

#### **Terminal Location:**

Back single mating end single contact grouping

## **Contact Material:**

Copper alloy 260 single mating end single contact grouping

## **Contact Surface Treatment:**

Gold single mating end single contact grouping and nickel single mating end single contact grouping

# **Insert Material:**

Plastic polyamide single mating end



# **Contact Surface Treatment Specification:** Mil-g-45204, type 2 military specification 1st treatment response single mating end single contact grouping and qq-n-290 federal specification 2nd treatment response single mating end single contact grouping **Terminal Type:** Printed circuit single mating end single contact grouping **Contact Material Specification:** Qq-b-613 federal specification single material response single mating end single contact grouping **Shell Material:** Aluminum alloy 6061 Shell Surface Treatment: Chromate Shell Surface Treatment Specification: Mil-c-5541 military specification single treatment response **Shell Material Specification:** Qq-a-200/8 federal specification single material response **Insert Material Specification:** Mil-p-20693, type 1 military specification single material response single mating end Unable To Decode: Unable to decode and unable to decode **Included Contact Quantity:** 39 single mating end single contact grouping **Included Contact Type:** Flat pin single mating end single contact grouping Color: Natural **Precious Material And Location:** Contact surfaces gold **Precious Material And Weight:** 0.039 gold grains, troy **Precious Material:** Gold **Specification Data:** 13499-372-0200 manufacturers specification control Shelf Life: N/a Unit Of Measure: **Demilitarization:** No Fiig: A039b0 Mil-std (military Standard): Mil-g-45204 spec.