

View Online at <https://aerobasegroup.com/nsn/5935-01-380-8272>

**Thread Class:**

2a

**Thread Direction:**

Right-hand

**Body Style:**

Straight shape, flange mount external coupling

**Overall Length:**

1.284 inches

**Overall Height:**

Between 1.684 inches and 1.704 inches

**Overall Width:**

Between 1.684 inches and 1.704 inches

**Unable To Decode:**

Unable to decode and unable to decode

**Unable To Decode:**

Unable to decode and unable to decode

**Center To Center Distance Between Mounting Facilities Parallel To Height:**

Between 1.250 inches and 1.375 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:**

Between 1.250 inches and 1.375 inches

**Threaded Device Type:**

Back shell

**Mating End Quantity:**

1

**Contact Position Arrangement Style:**

21-41 single mating end

**Contact Removability:**

Removable single mating end single contact grouping

**Contact Maximum Current Rating In Amps:**

7.5 single mating end single contact grouping

**Polarization Method:**

Key, multiple key groove

**Insert Position In Deg:**

49.0 and 169.0 and 200.0 and 244.0

**Shell Type:**

Solid

**Connector Locking Method:**

Detent

**Thready Qty Per Inch (tpi):**

28

**Thread Size:**

1.250 inches

**Terminal Location:**

Back single mating end single contact grouping

**Contact Material:**

Copper alloy single mating end single contact grouping

**Contact Surface Treatment:**

Gold single mating end single contact grouping

**Insert Material:**

Rubber silicone class q single mating end

**Terminal Type:**

Crimp single mating end single contact grouping

**Shell Material:**

Carbon graphite

**Shell Surface Treatment:**

Nickel alloy

**Included Contact Quantity:**

41 single mating end single contact grouping

**Included Contact Type:**

Round socket single mating end single contact grouping

**Precious Material And Location:**

Contact surfaces gold

**Precious Material:**

Gold

**Thread Series Designator:**

Un

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A039b0