## NSN 5935-01-381-4161

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-381-4161 **Thread Direction:** Right-hand **Body Style:** Straight shape, external coupling strain relief **Overall Length:** 57.0 millimeters **Overall Height:** 25.4 millimeters **Overall Width:** 25.4 millimeters Center To Center Distance Between Mounting Facilities Parallel To Height: 18.2 millimeters Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 18.2 millimeters **Cable Entrance Diameter:** 7.7 millimeters **Distance From Mounting Shoulder To Front Face:** 18.2 millimeters **Threaded Device Type:** Mounting hole **Mating End Quantity:** 1 **Contact Position Arrangement Style:** 10s-4 single mating end **Contact Removability:** Removable single mating end single contact grouping **Polarization Method:** Key, multiple key groove **Insert Position In Deg:** 0.0 Shell Type: **Connector Locking Method:** Bayonet slot **Connector Cable Strain Relief Method:** Compression nut **Thread Size:** 4.0 millimeters

**Terminal Location:** 

Back single mating end single contact grouping

**Contact Material:** 

Copper alloy single mating end single contact grouping

## NSN 5935-01-381-4161

Electrical Receptacle Connector - Page 2 of 2



Contact Surface Treatment:
Silver single mating end single contact grouping
Insert Material:
Plastic single mating end
Terminal Type:
Crimp single mating end single contact grouping
Shell Material:
Aluminum alloy
Shell Surface Treatment:
Cadmium and chromate
Thread Tolerance Class:
6h internal
Included Contact Quantity:
2 single mating end single contact grouping
Included Contact Type:
Round socket single mating end single contact grouping
Precious Material And Location:
Contact surfaces silver
Precious Material And Weight:
0.010 silver grains, troy
Precious Material:
Silver
Thread Series Designator:
Iso s
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0