NSN 5935-01-381-4204

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-381-4204

Body Style: Straight shape, internal coupling **Overall Length:** 3.897 inches **Overall Height:** 4.016 inches **Overall Width:** 3.875 inches **Unthreaded Mounting Hole Diameter:** 0.281 inches Center To Center Distance Between Mounting Facilities Parallel To Height: 3.156 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 3.156 inches **Mating End Quantity: Contact Position Arrangement Style:** 52-13 single mating end **Contact Removability:** Removable single mating end all contact groupings **Polarization Method:** Keyway or multiple keyway **Insert Position In Deg:** 0.0 and 240.0 and 225.0 and 210.0 Shell Type: Solid **Connector Locking Method:** Bayonet slot **Operating Tempurature Rating:** Between -55.0 degrees celsius and 125.0 degrees celsius **Terminal Location:** Back single mating end all contact groupings **Contact Material:** Copper alloy single mating end all contact groupings **Contact Surface Treatment:** Gold single mating end all contact groupings **Insert Material:** Plastic epoxy single mating end **Terminal Type:** Solder well single mating end all contact groupings **Shell Material:** Aluminum alloy

NSN 5935-01-381-4204

Mil-std (military Standard):

Mil-c-22992 spec.

Electrical Receptacle Connector - Page 2 of 2



Shell Surface Treatment:
Cadmium and chromate and nickel
Included Contact Quantity:
4 single mating end 2nd contact grouping
Included Contact Type:
Round pin single mating end all contact groupings
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.028 gold grains, troy
Precious Material:
Gold
Supplementary Features:
Mounting method - unthreaded hole
Test Data Document:
81349-mil-c-22992 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Specification Data:
96906-ms90558 government specification
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:
No
Fiig:
A039b0