

View Online at <https://aerobasegroup.com/nsn/5935-01-381-4257>

Body Material:

Rubber, synthetic

Thread Class:

2a

Thread Direction:

Right-hand

Body Style:

Top mount w/studs

Overall Length:

1.437 inches

Overall Height:

1.260 inches

Overall Width:

0.790 inches

Body Mounting Hole Accommodation Length:

1.075 inches

Body Mounting Hole Accommodation Width:

0.780 inches

Mounting Hole Style:

Rectangular, w/three mounting holes/slots

Contact Maximum Current Rating In Amps:

10.0

Contact Material:

Copper

Contact Surface Treatment:

Copper and gold

Accommodated Contact Quantity:

11

Center To Center Distance Between Outside Mounting Holes Along Length:

1.080 inches

Center To Center Distance Between Outside Mounting Holes Along Width:

0.500 inches

Projection Length Below Mounting Surface:

0.280 inches

Mounting Method:

Threaded hole

Mounting Type For Which Designed:

Chassis

Thready Qty Per Inch (tpi):

40

Thread Size:

0.112 inches

Contact Position Arrangement Style:

In-line

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.011 gold grains, troy

Precious Material:

Gold

Test Data Document:

81349--12883/46 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

Un

Terminal Type And Quantity:

11 crimp

Specification Data:

81349-mil-s-12883 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A02300