NSN 5935-01-381-7389

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/psn/5035-01-381-7380

view Online at https://aerobasegroup.com/nsn/5935-01-361-7369
Body Style:
Straight type
Overall Length:
0.800 inches
Overall Width:
0.200 inches
Body Height:
0.355 inches
Environmental Protection:
Thermal shock resistant and humidity resistant and vibration resistant and salt spray proof
Mating End Quantity:
1
Contact Position Arrangement Style:
2 rows of contacts non-inserted board single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
3.0 single mating end single contact grouping
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping and nickel single mating end single contact grouping
Insert Material:
Plastic polyester glass filled single mating end
Contact Surface Treatment Specification:
Mil-g-45204 military specification 1st treatment response single mating end single contact grouping and qq-n-290 federal specification 2nd
treatment response single mating end single contact grouping
Terminal Type:
Tab, solder lug single mating end single contact grouping
Contact Material Specification:
Qq-c-533 federal specification single material response single mating end single contact grouping
Insert Material Specification:
Mil-m-24519 military specification single material response single mating end
Included Contact Quantity:

16 single mating end single contact grouping

Included Contact Type:

Flat socket single mating end single contact grouping

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.016 gold grains, troy

NSN 5935-01-381-7389

Electrical Receptacle Connector - Page 2 of 2



Gold
Supplementary Features:
Mounting method - terminal
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0

Mil-std (military Standard):

Mil-g-45204 spec.

Precious Material: