NSN 5935-01-381-8198

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-381-8198

Body Style: Right angle type **Overall Length: 3.700** inches **Overall Width:** 0.325 inches **Body Height:** 0.238 inches **Mating End Quantity: Contact Position Arrangement Style:** 2 rows of contacts non-inserted board single mating end **Contact Removability:** Nonremovable single mating end 2nd contact grouping **Contact Maximum Current Rating In Amps:** 3.0 single mating end 2nd contact grouping **Polarization Method:** Mating end **Connector Locking Method:** Friction **Terminal Location:** Side single mating end 2nd contact grouping **Contact Material:** Copper alloy single mating end 2nd contact grouping **Contact Surface Treatment:** Gold single mating end 2nd contact grouping and nickel single mating end 2nd contact grouping **Contact Surface Treatment Specification:** Mil-g-45204, type 2, grade c, cl 1 military specification 1st treatment response single mating end 2nd contact grouping and qq-n-290, cl 2 federal specification 2nd treatment response single mating end 2nd contact grouping **Terminal Type:** Pin single mating end 2nd contact grouping **Contact Material Specification:** Qq-c-530 federal specification single material response single mating end 2nd contact grouping or qq-c-533 federal specification single material response single mating end 2nd contact grouping or qq-b-750 federal specification single material response single mating end 2nd contact grouping **Included Contact Quantity:** 76 single mating end single contact grouping **Included Contact Type:** Square socket single mating end 2nd contact grouping **Precious Material And Location:**

Cold

Contact surfaces gold

0.076 gold grams

Precious Material:

Precious Material And Weight:

NSN 5935-01-381-8198

Electrical Receptacle Connector - Page 2 of 2



Supplementary Features:
Mounting method - friction
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
Demilitarization: No
Jonna 1241.011

Mil-std (military Standard):

Mil-g-45204 spec.