## NSN 5935-01-382-0383

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-382-0383

Body Style:
Straight type
Overall Length:
4.350 inches
Overall Height:
0.335 inches
Overall Width:
0.250 inches
Environmental Protection:
Humidity resistant and vibration proof and corrosion resistan
Distance Between Mounting Facility Centers:
4.100 inches
Mating End Quantity:
1
Contact Position Arrangement Style:
70 single mating end
Contact Removability:
Removable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
5.0 single mating end single contact grouping
Contact Maximum Ac Voltage Rating In Volts:
1000.0 single mating end single contact grouping
Polarization Method:
Guide pin/socket
Shell Type:
Solid
Connector Locking Method:
Friction
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping
Terminal Type:
Printed circuit single mating end single contact grouping
Shell Material:
Plastic polyester
Unable To Decode:
Unable to decode and unable to decode
Included Contact Quantity:

meradea contact quantity

70 single mating end single contact grouping

## NSN 5935-01-382-0383

Electrical Receptacle Connector - Page 2 of 2



ın	ادام	ided	0	nto	~+	т.,	-
m	CIU	ıaea		mta	Ct	ıν	De:

Round socket single mating end single contact grouping

**Precious Material And Location:** 

Contact surfaces gold

**Precious Material And Weight:** 

0.070 gold grains, troy

Precious Material:

Gold

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A039b0