

View Online at <https://aerobasegroup.com/nsn/5935-01-382-0411>

Body Style:

Straight shape, external coupling

Overall Length:

1.581 inches

Overall Height:

1.496 inches

Overall Width:

1.496 inches

Environmental Protection:

Vibration resistant and corrosion resistant

Unthreaded Mounting Hole Diameter:

0.126 inches

Center To Center Distance Between Mounting Facilities Parallel To Height:

1.157 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

1.157 inches

Distance From Mounting Shoulder To Front Face:

0.748 inches

Mating End Quantity:

1

Contact Position Arrangement Style:

20-27 single mating end

Contact Removability:

Nonremovable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

22.0 single mating end single contact grouping

Contact Maximum Ac Voltage Rating In Volts:

500.0 single mating end single contact grouping

Contact Maximum Dc Voltage Rating In Volts:

700.0 single mating end single contact grouping

Polarization Method:

Keyway or multiple keyway

Insert Position In Deg:

0.0

Shell Type:

Solid

Connector Locking Method:

Bayonet latch

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Silver single mating end single contact grouping

Insert Material:

Rubber single mating end

Terminal Type:

Solder well single mating end single contact grouping

Shell Material:

Aluminum alloy

Shell Surface Treatment:

Cadmium and chromate

Included Contact Quantity:

14 single mating end single contact grouping

Included Contact Type:

Round socket single mating end single contact grouping

Precious Material And Location:

Coontact surfaces silver

Precious Material And Weight:

0.014 silver grains, troy

Precious Material:

Silver

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A039b0