

View Online at <https://aerobasegroup.com/nsn/5935-01-382-1442>

Body Style:

Straight type

Overall Length:

1.280 inches

Overall Height:

Between 0.380 inches and 0.420 inches

Overall Width:

0.250 inches

Unthreaded Mounting Hole Diameter:

0.098 inches

Distance Between Mounting Facility Centers:

1.000 inches

Mating End Quantity:

1

Contact Position Arrangement Style:

2 rows of contacts non-inserted board single mating end

Contact Removability:

Nonremovable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

1.5 single mating end single contact grouping

Connector Locking Method:

Friction

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping and nickel single mating end single contact grouping

Insert Material:

Plastic polyester single mating end and glass fiber single mating end

Contact Surface Treatment Specification:

Mil-g-45204, ty2, class1, grade c military specification 1st treatment response single mating end single contact grouping and qq-n-290, cl2 federal specification 2nd treatment response single mating end single contact grouping

Terminal Type:

Pin single mating end single contact grouping

Contact Material Specification:

Qq-b-626 federal specification single material response single mating end single contact grouping or qq-b-750 federal specification single material response single mating end single contact grouping or qq-c530 federal specification single material response single mating end single contact grouping

Insert Material Specification:

Mil-m-24519, ty gpt-30f military specification all material responses single mating end

Included Contact Quantity:

30 single mating end single contact grouping

Included Contact Type:

Flat socket single mating end single contact grouping

Special Features:

Altered from m55302/119-02

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.