NSN 5935-01-382-6218

Thread Direction:

Overall Length: 33.16 millimeters

Straight shape, internal coupling

Right-hand **Body Style:**

Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-382-6218

| Overall Diameter: |
|---|
| 25.0 millimeters |
| Environmental Protection: |
| Moisture proof and salt water resistant and vibration proof |
| Threaded Device Type: |
| Back shell |
| Mating End Quantity: |
| 1 |
| Contact Position Arrangement Style: |
| Afdx 11-5 single mating end |
| Contact Removability: |
| Removable single mating end single contact grouping |
| Polarization Method: |
| Keyway or multiple keyway |
| Insert Position In Deg: |
| 0.0 and 113.0 and 156.0 and 182.0 and 292.0 |
| Shell Type: |
| Solid |
| Connector Locking Method: |
| Internally threaded coupling ring |
| Thread Size: |
| 15.0 millimeters |
| Terminal Location: |
| Back single mating end single contact grouping |
| Contact Material: |
| Copper alloy single mating end single contact grouping |
| Contact Surface Treatment: |
| Gold single mating end single contact grouping |
| Terminal Type: |
| Crimp single mating end single contact grouping |
| Shell Material: |
| Aluminum alloy |
| Shell Surface Treatment: |
| Cadmium |
| Thread Tolerance Class: |
| 6g external |
| |

NSN 5935-01-382-6218

Electrical Plug Connector - Page 2 of 2



| ct Quantity: |
|--------------|
| |

5 single mating end single contact grouping

Included Contact Type:

Round pin single mating end single contact grouping

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.030 gold grains, troy

Precious Material:

Gold

Thread Series Designator:

Iso m

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0