

View Online at <https://aerobasegroup.com/nsn/5935-01-382-6288>

Body Style:

Straight shape

Overall Length:

0.740 inches

Overall Height:

0.385 inches

Overall Width:

0.282 inches

Environmental Protection:

Thermal shock resistant and humidity resistant and vibration resistant and shock resistant and salt spray proof

Board Accommodated Width:

0.288 inches

Mating End Quantity:

1

Contact Position Arrangement Style:

2 rows of independent contacts inserted board all mating ends

Contact Removability:

Nonremovable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

3.0 single mating end single contact grouping

Contact Maximum Ac Voltage Rating In Volts:

1000.0 single mating end single contact grouping

Shell Type:

Solid

Connector Locking Method:

Friction

Radio Frequency Type Contact Characteristic Impedance In Ohms:

5000.0 single mating end single contact grouping

Operating Temperature Rating:

Between -65.0 degrees celsius and 125.0 degrees celsius

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Beryllium single mating end single contact grouping and copper single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping

Insert Material:

Plastic diallyl phthalate glass filled all mating ends

Contact Surface Treatment Specification:

Mil-g-45204 military specification single treatment response single mating end single contact grouping and qq-n-290 federal specification single treatment response single mating end single contact grouping and mil-p-81728 military specification single treatment response single mating end single contact grouping

Terminal Type:

Pin single mating end single contact grouping

Contact Material Specification:

Astim b194, 1/2 hard. Mfr ref single material response single mating end single contact grouping

Shell Material:

Plastic diallyl phthalate

Shell Surface Treatment:

Gold

Shell Surface Treatment Specification:

Mil-g-45204 federal specification single treatment response

Shell Material Specification:

Mil-m-14 military specification single material response

Insert Material Specification:

Mil-m-14 military specification single material response all mating ends

Included Contact Quantity:

10 single mating end single contact grouping

Included Contact Type:

Square socket single mating end single contact grouping

Precious Material And Location:

Internal surfaces gold

Precious Material:

Gold

Supplementary Features:

Mounting method - friction

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.