

View Online at <https://aerobasegroup.com/nsn/5935-01-382-7560>

**Thread Class:**

2a

**Thread Direction:**

Right-hand

**Body Style:**

Straight shape, external coupling

**Overall Length:**

0.530 inches

**Overall Height:**

0.161 inches

**Overall Width:**

0.187 inches

**Environmental Protection:**

Thermal shock resistant and corrosion resistant and vibration resistant and vibration resistant

**Threaded Device Type:**

Mounting bushing

**Mating End Quantity:**

1

**Contact Position Arrangement Style:**

Rf single mating end

**Contact Removability:**

Nonremovable single mating end single contact grouping

**Contact Maximum Ac Voltage Rating In Volts:**

250.0 single mating end single contact grouping

**Contact Maximum Frequency Rating:**

4.0 gigahertz single mating end single contact grouping

**Shell Type:**

Solid

**Connector Locking Method:**

Push-pull

**Radio Frequency Type Contact Characteristic Impedance In Ohms:**

50.0 single mating end single contact grouping

**Operating Temperature Rating:**

Between -65.0 degrees celsius and 165.0 degrees celsius

**Thread Size:**

0.138 inches

**Terminal Location:**

Back single mating end single contact grouping

**Contact Material:**

Copper alloy single mating end single contact grouping

**Contact Surface Treatment:**

Gold single mating end single contact grouping

**Insert Material:**

Plastic fluorinated ethylene propylene single mating end or plastic polytetrafluoroethylene single mating end

**Terminal Type:**

Turret single mating end single contact grouping

**Included Contact Quantity:**

1 single mating end single contact grouping

**Bushing Accommodation Hole Shape:**

Round w/flat

**Included Contact Type:**

Coaxial pin single mating end single contact grouping

**Precious Material And Location:**

Contact surfaces gold

**Precious Material And Weight:**

0.005 gold grains, troy

**Precious Material:**

Gold

**Thread Series Designator:**

Unf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiiig:**

A039b0