NSN 5935-01-382-8935

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-382-8935

Body Style: Rectangular shape, angle **Overall Length:** 2.729 inches **Overall Height:** 0.593 inches **Overall Width:** 0.668 inches **Environmental Protection:** Corrosion resistant and humidity resistant and shock resistant and vibration resistant **Unthreaded Mounting Hole Diameter:** 0.162 inches **Distance Between Mounting Facility Centers:** 2.500 inches **Mating End Quantity: Contact Position Arrangement Style:** 37 single mating end **Contact Removability:** Nonremovable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 7.0 single mating end single contact grouping **Polarization Method:** Mating end Shell Type: Solid **Connector Locking Method:** Friction **Operating Tempurature Rating:** Between -55.0 degrees celsius and 125.0 degrees celsius **Terminal Location:** Side single mating end single contact grouping **Contact Material:** Copper alloy 172 single mating end single contact grouping **Contact Surface Treatment:** Gold single mating end single contact grouping and nickel single mating end single contact grouping **Insert Material:** Plastic polyphenylene single mating end **Contact Surface Treatment Specification:** Mil-g-45204, type 2, grade c military specification 1st treatment response single mating end single contact grouping and qq-n-290, cl 2 federal specification 2nd treatment response single mating end single contact grouping

Terminal Type:

Pin single mating end single contact grouping

NSN 5935-01-382-8935

Electrical Receptacle Connector - Page 2 of 2



Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.