## NSN 5935-01-383-1955

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-383-1955

Body Style:
Rectangular shape w/clamp
Overall Length:
1.920 inches
Overall Height:
1.608 inches
Overall Width:
0.610 inches
Environmental Protection:
Moisture proof and vibration proof and shock proof and salt water resistant
Cable Entrance Diameter:
0.473 inches
Mating End Quantity:
1
Contact Position Arrangement Style:
24 single mating end
Contact Maximum Current Rating In Amps:
5.0 single mating end single contact grouping
Contact Maximum Ac Voltage Rating In Volts:
1000.0 single mating end single contact grouping
Contact Maximum Dc Voltage Rating In Volts:
700.0 single mating end single contact grouping
Polarization Method:
Mating end
Connector Locking Method:
Friction
Connector Cable Strain Relief Method:
Cable clamp
Cable Opening Length:
0.473 inches
Cable Opening Width:
0.473 inches
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Cadmium single mating end single contact grouping and copper single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping
Insert Material:
Plastic diallyl phthalate single mating end
Contact Surface Treatment Specification:

Mil-g-45204 military specification single treatment response single mating end single contact grouping

## NSN 5935-01-383-1955

Electrical Receptacle Connector - Page 2 of 2



Terminal Type:
Crimp single mating end single contact grouping
Shell Material:
Copper alloy
Shell Surface Treatment:
Nickel
Shell Surface Treatment Specification:
Qq-n-290 federal specification single treatment response
Shell Material Specification:
Qq-n-290 federal specification single material response
Insert Material Specification:
Mil-c-19833 military specification single material response single mating end or mil-m-14 military specification single material response single
mating end
Included Contact Quantity:
24 single mating end single contact grouping
Included Contact Type:
Square socket single mating end single contact grouping
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.024 gold grams
Precious Material:
Gold
Supplementary Features:
Mounting method - friction
Shelf Life:
N/a
Unit Of Measure:
<del>-</del>
Demilitarization:
No
Fiig:
A039b0
Mil-std (military Standard):
Mil-g-45204 spec.