# NSN 5935-01-383-3973

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-383-3973

**Body Style:** 

Straight shape, flush mount

**Overall Length:** 

1.634 inches

**Overall Height:** 

Between 3.060 inches and 3.090 inches

**Overall Width:** 

Between 1.985 inches and 2.015 inches

**Environmental Protection:** 

Humidity resistant and salt water resistant and shock resistant and thermal shock resistant and vibration resistant

**Unthreaded Mounting Hole Diameter:** 

Between 0.118 inches and 0.122 inches

Center To Center Distance Between Mounting Facilities Parallel To Height:

**2.783** inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

1.438 inches

**Distance From Mounting Shoulder To Front Face:** 

Between 0.055 inches and 0.065 inches

**Mating End Quantity:** 

2

**Contact Position Arrangement Style:** 

32c2 1st mating end

**Contact Removability:** 

Removable all mating ends single contact grouping

**Polarization Method:** 

Mating end and 3 polarization posts

Shell Type:

Solid

**Connector Locking Method:** 

Friction

**Terminal Location:** 

Back all mating ends single contact grouping

**Contact Material:** 

Copper alloy single mating end single contact grouping

**Contact Surface Treatment:** 

Gold all mating ends single contact grouping

**Insert Material:** 

Plastic diallyl phthalate glass filled all mating ends or plastic epoxy all mating ends or plastic phenolic all mating ends

**Contact Surface Treatment Specification:** 

Mil-g-45204, type 2, grade c, cl 1 military specification single treatment response all mating ends single contact grouping

**Terminal Type:** 

Crimp all mating ends single contact grouping

# NSN 5935-01-383-3973

Electrical Receptacle Connector - Page 2 of 2



### **Guide Design And Location:**

Hexagon shape female post left-hand at 6 oclock and hexagon shape female post center at 6 oclock and hexagon shape female post right-hand at 6 oclock

#### **Shell Material:**

Aluminum alloy

#### **Shell Surface Treatment:**

Nickel

#### **Shell Surface Treatment Specification:**

Mil-c-26074 military specification single treatment response

#### **Shell Material Specification:**

Qq-a-591 federal specification single material response or qq-a-367 federal specification single material response or qq-a-250 federal specification single material response

### **Insert Material Specification:**

Mil-m-14, ty gdi-30f or sdg-f military specification 1st material response all mating ends or allied chemical 1288 bx mfr ref 2nd material response all mating ends or mil-m-14 military specification 3rd material response all mating ends

#### **Included Contact Quantity:**

30 1st mating end 2nd contact grouping

#### **Included Contact Type:**

Round socket 2nd mating end single contact grouping

#### **Precious Material And Weight:**

0.146 gold grains, troy

## **Precious Material:**

Gold

## **Test Data Document:**

81349-mil-c-81659 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

### **Specification Data:**

81349-mil-c-81659/35 government specification

Shelf Life:

N/a

**Unit Of Measure:** 

**Demilitarization:** 

No

Fiig:

A039b0

# Mil-std (military Standard):

Mil-g-45204 spec.