NSN 5935-01-383-3981

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-383-3981 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Straight shape, external coupling **Overall Length:** 1.380 inches **Overall Diameter:** 0.690 inches **Environmental Protection:** Corrosion resistant **Unthreaded Mounting Hole Diameter:** 0.510 inches **Cable Entrance Diameter:** 0.120 inches **Distance From Mounting Shoulder To Front Face:** 0.810 inches **Mounting Facility Thickness:** 0.241 inches **Threaded Device Type:** Mounting bushing **Mating End Quantity: Contact Position Arrangement Style:** Bnc single mating end **Contact Removability:** Nonremovable single mating end single contact grouping **Contact Maximum Frequency Rating:** 4.0 gigahertz single mating end single contact grouping Shell Type: **Connector Locking Method:** Bayonet pin **Operating Tempurature Rating:** Between -65.0 degrees celsius and 165.0 degrees celsius **Thread Size:** 0.500 inches

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

NSN 5935-01-383-3981

Electrical Receptacle Connector - Page 2 of 2



Contact Surface Treatment: Nickel single mating end single contact grouping **Insert Material:** Plastic polytetrafluoroethylene single mating end **Terminal Type:** Crimp single mating end single contact grouping **Shell Material:** Copper alloy **Shell Surface Treatment:** Nickel alloy **Included Contact Quantity:** 1 single mating end single contact grouping **Included Contact Type:** Round socket single mating end single contact grouping **Supplementary Features:** Mounting method - jam mut **Thread Series Designator:** Unef Shelf Life: N/a **Unit Of Measure:** Demilitarization: No

Fiig: A039b0