

View Online at <https://aerobasegroup.com/nsn/5935-01-383-4124>

**Thread Class:**

2b

**Thread Direction:**

Right-hand

**Body Style:**

Straight shape

**Overall Length:**

1.265 inches

**Overall Height:**

Between 1.146 inches and 1.170 inches

**Overall Width:**

Between 3.000 inches and 3.030 inches

**Environmental Protection:**

Humidity resistant and shock proof and corrosion resistant and vibration resistant and thermal shock resistant

**Center To Center Distance Between Mounting Facilities Parallel To Height:**

Between 0.558 inches and 0.566 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:**

Between 2.570 inches and 2.580 inches

**Distance From Mounting Shoulder To Front Face:**

Between 0.615 inches and 0.630 inches

**Threaded Device Type:**

Mounting hole

**Mating End Quantity:**

1

**Contact Position Arrangement Style:**

"18, 018" single mating end

**Contact Removability:**

Removable single mating end single contact grouping

**Polarization Method:**

Mating end

**Shell Type:**

Solid

**Connector Locking Method:**

Friction

**Operating Temperature Rating:**

Between 65.0 degrees celsius and 200.0 degrees celsius

**Thread Size:**

0.138 inches

**Terminal Location:**

Back single mating end single contact grouping

**Contact Material:**

Copper alloy single mating end single contact grouping

**Contact Surface Treatment:**

Gold single mating end single contact grouping

**Insert Material:**

Plastic single mating end

**Contact Surface Treatment Specification:**

Mil-c-45204, ty2, grade c, cl 1 military specification single treatment response single mating end single contact grouping

**Terminal Type:**

Crimp single mating end single contact grouping

**Contact Material Specification:**

Qq-c-533 federal specification single material response single mating end single contact grouping

**Shell Material:**

Aluminum alloy

**Shell Surface Treatment:**

Nickel

**Shell Surface Treatment Specification:**

Mil-c-26074, gradea, cl3or4 military specification single treatment response

**Shell Material Specification:**

Qq-a-591 federal specification single material response

**Included Contact Quantity:**

18 single mating end single contact grouping

**Included Contact Type:**

Round socket single mating end single contact grouping

**Precious Material And Location:**

Contact surfaces gold

**Precious Material:**

Gold

**Supplementary Features:**

Mounting method - spring

**Thread Series Designator:**

Unc

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A039b0

**Mil-std (military Standard):**

Mil-c-45204 spec.