## NSN 5935-01-383-4292

Electrical Receptacle Connector - Page 1 of 3



View Online at https://aerobasegroup.com/nsn/5935-01-383-4292 **Thread Class:** 2a **Thread Direction:** Left-hand **Body Style:** Straight shape, external coupling **Unable To Decode:** Unable to decode and unable to decode **Overall Length:** 2.016 inches **Overall Height:** 2.750 inches **Overall Width:** 2.750 inches **Environmental Protection:** Humidity resistant and moisture resistant and corrosion resistant and chemical resistant and dust resistant and shock resistant and vibration resistant **Unthreaded Mounting Hole Diameter:** 0.218 inches Center To Center Distance Between Mounting Facilities Parallel To Height: 2.090 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 2.090 inches **Distance From Mounting Shoulder To Front Face:** 1.000 inches **Threaded Device Type:** Coupling facility **Mating End Quantity: Contact Position Arrangement Style:** 20-37 single mating end **Contact Removability:** Nonremovable single mating end single contact grouping **Polarization Method:** Keyway or multiple keyway **Insert Position In Deg:** 0.0 Shell Type:

Compression nut

**Connector Locking Method:** Externally threaded shell

**Connector Cable Strain Relief Method:** 

Solid

## NSN 5935-01-383-4292

Electrical Receptacle Connector - Page 2 of 3



End Application:
•
Lgm-30 minuteman missle
Operating Tempurature Rating:
Between -67.0 degrees fahrenheit and 257.0 degrees fahrenheit
Features Provided:
Captive contact
Thready Qty Per Inch (tpi):
8
Thread Size:
2.500 inches
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Silver single mating end single contact grouping
Contact Surface Treatment Specification:
Qq-s-365 federal specification single treatment response single mating end single contact grouping
Terminal Type:
Crimp single mating end single contact grouping
Shell Material:
Aluminum alloy 6061
Shell Surface Treatment:
Anodize
Included Contact Quantity:
5 single mating end single contact grouping
Included Contact Type:
Round socket single mating end single contact grouping
Special Features:
Furnished items - protective cover and chain
Precious Material And Location:
Contact surfaces silver
Precious Material And Weight:
0.025 silver grains, troy
Precious Material:
Silver
Thread Series Designator:
Special acme
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:

No

## NSN 5935-01-383-4292

Electrical Receptacle Connector - Page 3 of 3



Fiig:

A039b0