

View Online at <https://aerobasegroup.com/nsn/5935-01-383-4851>

Body Style:

Straight shape

Overall Length:

3.118 inches

Overall Diameter:

Between 0.826 inches and 0.836 inches

Environmental Protection:

Shock resistant and vibration resistant and thermal shock resistant and salt water resistant and humidity resistant and waterproof

Cable Entrance Diameter:

0.320 inches

Mating End Quantity:

1

Contact Position Arrangement Style:

6 single mating end

Contact Removability:

Nonremovable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

0.5 single mating end single contact grouping

Contact Maximum Ac Voltage Rating In Volts:

60.0 single mating end single contact grouping

Polarization Method:

Key, multiple key groove

Insert Position In Deg:

0.0 and 145.0

Shell Type:

Solid

Connector Locking Method:

Friction

Connector Cable Strain Relief Method:

Compression nut and grommet

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy 360 single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping and nickel single mating end single contact grouping

Insert Material:

Plastic diallyl phthalate single mating end

Contact Surface Treatment Specification:

Mil-g-45204, type 1, grade c, cl 0 military specification 1st treatment response single mating end single contact grouping and qq-n-290, cl1, grade c federal specification 2nd treatment response single mating end single contact grouping

Contact Material Specification:

Qq-b-626, 1/2 hard federal specification single material response single mating end single contact grouping

Shell Material:

Stainless steel

Shell Surface Treatment:

Passivate

Shell Surface Treatment Specification:

Mil-f-14072 ty e300 military specification single treatment response

Shell Material Specification:

Astm a582 assn standard single material response

Insert Material Specification:

Mil-m+14 ty sdg-f or gdf-30-f or mdg military specification single material response single mating end

Included Contact Quantity:

6 single mating end single contact grouping

Included Contact Type:

Round pin single mating end single contact grouping

Special Features:

Solder cup terminals

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.005 gold grains, troy

Precious Material:

Gold

Test Data Document:

81349-mil-c-55116 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Specification Data:

81349-mil-c-55116/1 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.