## NSN 5935-01-384-2054

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-384-2054 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Straight shape, external coupling **Overall Length:** 1.625 inches **Overall Height:** Between 1.363 inches and 1.403 inches **Overall Width:** Between 1.363 inches and 1.625 inches **Environmental Protection:** Moisture resistant and corrosion resistant and thermal shock resistant and vibration resistant and heat resistant and cold resistant **Unthreaded Mounting Hole Diameter:** Between 0.115 inches and 0.130 inches **Center To Center Distance Between Mounting Facilities Parallel To Height:** 1.015 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 1.015 inches **Distance From Mounting Shoulder To Front Face:** Between 0.878 inches and 0.898 inches **Threaded Device Type:** Coupling facility **Mating End Quantity: Contact Position Arrangement Style:** 17-31 single mating end **Contact Removability:** Removable single mating end single contact grouping **Polarization Method:** Keyway or multiple keyway **Insert Position In Deg:** 88.0 and 163.0 and 207.0 and 281.0 **Shell Type:** Solid **Connector Locking Method:** 

Externally threaded shell

Thready Qty Per Inch (tpi):

10

**Thread Size:** 

1.125 inches

## NSN 5935-01-384-2054

Fiig: A039b0

Electrical Receptacle Connector - Page 2 of 2



| Terminal Location:   |
|--|
| Back single mating end single contact grouping   |
| Contact Material:  |
| Copper alloy single mating end single contact grouping   |
| Contact Surface Treatment:   |
| Gold single mating end single contact grouping   |
| Insert Material:   |
| Plastic fluorosilicone single mating end   |
| Terminal Type:   |
| Crimp single mating end single contact grouping  |
| Shell Material:  |
| Aluminum   |
| Shell Surface Treatment:   |
| Cadmium and chromate and nickel  |
| Shell Surface Treatment Specification:   |
| Qq-p-416, type 2, cl 3 federal specification 1st treatment response  |
| Included Contact Quantity:   |
| 31 single mating end single contact grouping   |
| Included Contact Type:   |
| Round socket single mating end single contact grouping   |
| Precious Material And Location:  |
| Contact surfaces gold  |
| Precious Material:   |
| Gold   |
| Test Data Document:  |
| 81349-mil-dtl-28840 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification |
| format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain            |
| environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).                              |
| Thread Series Designator:  |
| Double stub  |
| Specification Data:  |
| 81349-mil-dtl-28840/12 government specification  |
| Shelf Life:  |
| N/a  |
| Unit Of Measure:   |
|  |
| Demilitarization:  |
| No   |