Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-384-2054

Threa	nd Class:
2a	
Threa	nd Direction:
Right-	hand
Body	Style:
Straig	ht shape, external coupling
Overa	all Length:
1.625	inches
Overa	all Height:
Betwe	een 1.363 inches and 1.403 inches
Overa	all Width:
Betwe	een 1.363 inches and 1.625 inches
Enviro	onmental Protection:
Moistu	ure resistant and corrosion resistant and thermal shock resistant and vibration resistant and heat resistant and cold resistant
Unthr	readed Mounting Hole Diameter:
Betwe	een 0.115 inches and 0.130 inches
Cente	er To Center Distance Between Mounting Facilities Parallel To Height:
1.015	inches
Distar	nce Between Centerlines Of Mounting Facilities Parallel To Body Width:
1.015	inches
Distar	nce From Mounting Shoulder To Front Face:
Betwe	een 0.878 inches and 0.898 inches
Threa	Ided Device Type:
Coupli	ing facility
Mating	g End Quantity:
1	
Conta	act Position Arrangement Style:
17-31	single mating end
Conta	act Removability:
Remo	vable single mating end single contact grouping
Polari	ization Method:
Keywa	ay or multiple keyway
Insert	t Position In Deg:
88.0 a	and 163.0 and 207.0 and 281.0
Shell	Туре:
Solid	
Conne	ector Locking Method:
Extern	nally threaded shell
Threa	ndy Qty Per Inch (tpi):
10	
Threa	nd Size:
1.125	inches



Terminal Location	1:
Back single mating	end single contact grouping
Contact Material:	
Copper alloy single	e mating end single contact grouping
Contact Surface 1	Freatment:
Gold single mating	end single contact grouping
Insert Material:	
Plastic fluorosilicor	ne single mating end
Terminal Type:	
Crimp single matin	g end single contact grouping
Shell Material:	
Aluminum	
Shell Surface Trea	atment:
Cadmium and chro	mate and nickel
Shell Surface Trea	atment Specification:
Qq-p-416, type 2,	cl 3 federal specification 1st treatment response
Included Contact	Quantity:
31 single mating er	nd single contact grouping
Included Contact	Туре:
Round socket sing	le mating end single contact grouping
Precious Material	And Location:
Contact surfaces g	old
Precious Material	:
Gold	
Test Data Docum	ent:
81349-mil-dtl-2884	0 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes c	commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and	performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Thread Series Des	signator:
Double stub	
Specification Data	a:
81349-mil-dtl-2884	0/12 government specification
Shelf Life:	
N/a	
Unit Of Measure:	
Demilitarization:	
No	
Fiig:	
A039b0	