

View Online at <https://aerobasegroup.com/nsn/5935-01-384-2569>

**Body Material:**

Brass

**Body Style:**

Top mount

**Overall Length:**

0.800 inches

**Temperature Rating:**

0.0 degrees celsius and 65.0 degrees celsius

**Overall Height:**

0.290 inches

**Overall Width:**

0.400 inches

**Mounting Hole Diameter:**

Between 0.017 inches and 0.023 inches

**Body Mounting Hole Accommodation Length:**

0.110 inches

**Body Mounting Hole Accommodation Width:**

Between 0.017 inches and 0.023 inches

**Mounting Hole Style:**

Rectangular, w/four mounting holes/slots

**Contact Resistance In Ohms:**

0.015

**Contact Maximum Current Rating In Amps:**

3.0

**Contact Material:**

Beryllium copper

**Contact Surface Treatment:**

Gold and nickel

**Accommodated Contact Quantity:**

16

**Resistor Rating:**

0.015 ohms and 20.0 megohms

**Center To Center Distance Between Outside Mounting Holes Along Length:**

0.800 inches

**Center To Center Distance Between Outside Mounting Holes Along Width:**

0.300 inches

**Printed Circuit Board Hole Arrangement Style:**

Ten hole dimension "a" 0.300 inch

**Component Shield Mounting Method:**

Force fit

**Polarization Type:**

Contact size

**Projection Length Above Mounting Surface:**

0.105 inches

**Mounting Method:**

Press fit

**Mounting Type For Which Designed:**

Printed circuit or chassis

**Contact Position Arrangement Style:**

Dual in-line

**Contact Maximum Voltage In Volts And Current Type:**

1200.0 ac

**Precious Material And Location:**

Internal surfaces gold

**Precious Material:**

Gold

**Terminal Type And Quantity:**

16 solder stud

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A02300