

View Online at <https://aerobasegroup.com/nsn/5935-01-384-2569>

Body Material:

Brass

Body Style:

Top mount

Overall Length:

0.800 inches

Temperature Rating:

0.0 degrees celsius and 65.0 degrees celsius

Overall Height:

0.290 inches

Overall Width:

0.400 inches

Mounting Hole Diameter:

Between 0.017 inches and 0.023 inches

Body Mounting Hole Accommodation Length:

0.110 inches

Body Mounting Hole Accommodation Width:

Between 0.017 inches and 0.023 inches

Mounting Hole Style:

Rectangular, w/four mounting holes/slots

Contact Resistance In Ohms:

0.015

Contact Maximum Current Rating In Amps:

3.0

Contact Material:

Beryllium copper

Contact Surface Treatment:

Gold and nickel

Accommodated Contact Quantity:

16

Resistor Rating:

0.015 ohms and 20.0 megohms

Center To Center Distance Between Outside Mounting Holes Along Length:

0.800 inches

Center To Center Distance Between Outside Mounting Holes Along Width:

0.300 inches

Printed Circuit Board Hole Arrangement Style:

Ten hole dimension "a" 0.300 inch

Component Shield Mounting Method:

Force fit

Polarization Type:

Contact size

Projection Length Above Mounting Surface:

0.105 inches

Mounting Method:

Press fit

Mounting Type For Which Designed:

Printed circuit or chassis

Contact Position Arrangement Style:

Dual in-line

Contact Maximum Voltage In Volts And Current Type:

1200.0 ac

Precious Material And Location:

Internal surfaces gold

Precious Material:

Gold

Terminal Type And Quantity:

16 solder stud

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A02300