## NSN 5935-01-384-3582

**Thread Class:** 

Right-hand

**Thread Direction:** 

2a

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-384-3582

Body Style:
Straight shape, external coupling
Overall Length:
2.047 inches
Overall Diameter:
2.203 inches
Environmental Protection:
Corrosion resistant
Distance From Mounting Shoulder To Front Face:
0.772 inches
Mounting Facility Thickness:
0.250 inches
Threaded Device Type:
Back shell and coupling facility
Mating End Quantity:
1
Contact Position Arrangement Style:
3 single mating end
Contact Removability:
Removable single mating end single contact grouping
Polarization Method:
Keyway or multiple keyway
Insert Position In Deg:
0.0
Shell Type:
Solid
Connector Locking Method:
Bayonet pin
Thread Size:
1.438 inches and 1.625 inches
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping
Insert Material:
Plastic single mating end

## NSN 5935-01-384-3582

Electrical Receptacle Connector - Page 2 of 2



Terminal Type:
Crimp single mating end single contact grouping
Shell Material:
Aluminum alloy
Shell Surface Treatment:
Cadmium and chromium
Included Contact Quantity:
3 single mating end single contact grouping
Bushing Accommodation Hole Shape:
Round w/flat
Included Contact Type:
Round pin single mating end single contact grouping
Special Features:
Contact designation 24-03
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.015 gold grains, troy
Precious Material:
Gold
Thread Series Designator:
Unef
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0