## NSN 5935-01-384-6783

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/psp/5035-01-384-6783

view Online at https://aerobasegroup.com/nsn/5955-01-564-6765
Thread Class:
2a and 2b and 2a
Thread Direction:
Right-hand
Body Style:
Straight shape
Overall Length:
Between 1.480 inches and 1.520 inches
Overall Height:
Between 0.605 inches and 0.645 inches
Overall Width:
Between 0.370 inches and 0.410 inches
Distance Between Mounting Facility Centers:
Between 1.276 inches and 1.286 inches
Threaded Device Type:
Coupling facility and mounting stud
Mating End Quantity:
1
Contact Position Arrangement Style:
44 single mating end
Polarization Method:
Jackscrew
Connector Locking Method:
Jackscrew-socket
End Application:
Pacer dawn
Thready Qty Per Inch (tpi):
56 and 56 and 56
Thread Size:
0.086 inches and 0.086 inches and 0.086 inches
Terminal Location:
Back single mating end single contact grouping
Insert Material:
Plastic polyphenylene single mating end
Insert Material Specification:
Mil-m-24519 type gst-40f military specification single material response single mating end
Included Contact Quantity:
44 single mating end single contact grouping
Included Contact Type:
Round socket single mating end single contact grouping
Supplementary Features:
Mounting method - stud

Mounting method - stud

## NSN 5935-01-384-6783

Electrical Receptacle Connector - Page 2 of 2



Thread Series Designator:
Unc and unc and unc
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
<b>Demilitarization:</b> No

Mil-std (military Standard):

Mil-m-24519 spec.