

View Online at https://aerobasegroup.com/nsn/5935-01-384-6899

| Thread Class:  |
|--|
| 2a   |
| Thread Direction:  |
| Right-hand   |
| Body Style:  |
| Straight shape, external coupling  |
| Overall Length:  |
| 1.937 inches   |
| Overall Height:  |
| 1.375 inches   |
| Overall Width:   |
| 1.375 inches   |
| Unthreaded Mounting Hole Diameter:   |
| 0.120 inches   |
| Center To Center Distance Between Mounting Facilities Parallel To Height:            |
| 1.062 inches   |
| Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:          |
| 1.062 inches   |
| Distance From Mounting Shoulder To Front Face:                                       |
| 0.750 inches   |
| Threaded Device Type:  |
| Coupling facility  |
| Mating End Quantity:   |
| 1  |
| Contact Position Arrangement Style:  |
| 18-1 single mating end   |
| Polarization Method:   |
| Keyway or multiple keyway  |
| Insert Position In Deg:  |
| 290.0  |
| Shell Type:  |
| Solid  |
| Connector Locking Method:  |
| Externally threaded shell  |
| Thread Size:   |
| 1.125 inches   |
| Insert Material:   |
| Rubber silicone class q single mating end  |
| Shell Surface Treatment:   |
| Cadmium and chromate and nickel  |
| Test Data Document:  |
| 81349-mil-c-5015 specification (includes engineering type bulletins, brochures, etc. |
|  |

81349-mil-c-5015 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Electrical Receptacle Connector Body - Page 2 of 2



**Thread Series Designator:** 

Unef

Specification Data:

96906-ms3402 government standard

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-c-5015 spec.