NSN 5935-01-384-6985

Connector Adapter - Page 1 of 2

Thread Class:

2a



View Online at https://aerobasegroup.com/nsn/5935-01-384-6985

Thread Direction:
Right-hand
Body Style:
Straight shape
Overall Length:
Between 1.376 inches and 1.400 inches
Overall Diameter:
0.600 inches
Threaded Device Type:
Coupling facility
Mating End Quantity:
2
Contact Position Arrangement Style:
Tnc 2nd mating end
Contact Removability:
Removable all mating ends single contact grouping
Contact Maximum Frequency Rating:
11.0 gigahertz all mating ends single contact grouping
Shell Type:
Solid
Connector Locking Method:
Externally threaded shell
Externally threaded shell Radio Frequency Type Contact Characteristic Impedance In Ohms:
•
Radio Frequency Type Contact Characteristic Impedance In Ohms:
Radio Frequency Type Contact Characteristic Impedance In Ohms: 50.0 all mating ends single contact grouping
Radio Frequency Type Contact Characteristic Impedance In Ohms: 50.0 all mating ends single contact grouping Thread Size:
Radio Frequency Type Contact Characteristic Impedance In Ohms: 50.0 all mating ends single contact grouping Thread Size: 0.625 inches and 0.438 inches
Radio Frequency Type Contact Characteristic Impedance In Ohms: 50.0 all mating ends single contact grouping Thread Size: 0.625 inches and 0.438 inches Contact Material:
Radio Frequency Type Contact Characteristic Impedance In Ohms: 50.0 all mating ends single contact grouping Thread Size: 0.625 inches and 0.438 inches Contact Material: Copper alloy all mating ends single contact grouping
Radio Frequency Type Contact Characteristic Impedance In Ohms: 50.0 all mating ends single contact grouping Thread Size: 0.625 inches and 0.438 inches Contact Material: Copper alloy all mating ends single contact grouping Contact Surface Treatment:
Radio Frequency Type Contact Characteristic Impedance In Ohms: 50.0 all mating ends single contact grouping Thread Size: 0.625 inches and 0.438 inches Contact Material: Copper alloy all mating ends single contact grouping Contact Surface Treatment: Gold all mating ends single contact grouping
Radio Frequency Type Contact Characteristic Impedance In Ohms: 50.0 all mating ends single contact grouping Thread Size: 0.625 inches and 0.438 inches Contact Material: Copper alloy all mating ends single contact grouping Contact Surface Treatment: Gold all mating ends single contact grouping Insert Material:
Radio Frequency Type Contact Characteristic Impedance In Ohms: 50.0 all mating ends single contact grouping Thread Size: 0.625 inches and 0.438 inches Contact Material: Copper alloy all mating ends single contact grouping Contact Surface Treatment: Gold all mating ends single contact grouping Insert Material: Plastic polytetrafluoroethylene all mating ends
Radio Frequency Type Contact Characteristic Impedance In Ohms: 50.0 all mating ends single contact grouping Thread Size: 0.625 inches and 0.438 inches Contact Material: Copper alloy all mating ends single contact grouping Contact Surface Treatment: Gold all mating ends single contact grouping Insert Material: Plastic polytetrafluoroethylene all mating ends Shell Material:
Radio Frequency Type Contact Characteristic Impedance In Ohms: 50.0 all mating ends single contact grouping Thread Size: 0.625 inches and 0.438 inches Contact Material: Copper alloy all mating ends single contact grouping Contact Surface Treatment: Gold all mating ends single contact grouping Insert Material: Plastic polytetrafluoroethylene all mating ends Shell Material: Copper alloy
Radio Frequency Type Contact Characteristic Impedance In Ohms: 50.0 all mating ends single contact grouping Thread Size: 0.625 inches and 0.438 inches Contact Material: Copper alloy all mating ends single contact grouping Contact Surface Treatment: Gold all mating ends single contact grouping Insert Material: Plastic polytetrafluoroethylene all mating ends Shell Material: Copper alloy Shell Surface Treatment:
Radio Frequency Type Contact Characteristic Impedance In Ohms: 50.0 all mating ends single contact grouping Thread Size: 0.625 inches and 0.438 inches Contact Material: Copper alloy all mating ends single contact grouping Contact Surface Treatment: Gold all mating ends single contact grouping Insert Material: Plastic polytetrafluoroethylene all mating ends Shell Material: Copper alloy Shell Surface Treatment: Silver and chromate
Radio Frequency Type Contact Characteristic Impedance In Ohms: 50.0 all mating ends single contact grouping Thread Size: 0.625 inches and 0.438 inches Contact Material: Copper alloy all mating ends single contact grouping Contact Surface Treatment: Gold all mating ends single contact grouping Insert Material: Plastic polytetrafluoroethylene all mating ends Shell Material: Copper alloy Shell Surface Treatment: Silver and chromate Included Contact Quantity:

NSN 5935-01-384-6985

Connector Adapter - Page 2 of 2



Precious Material And Location

Contact surfaces gold and body surfaces silver

Precious Material And Weight:

0.010 gold grains, troy and 0.100 silver grains, troy

Precious Material:

Gold and silver

Thread Series Designator:

Unef

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0