Electrical Receptacle Connector - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5935-01-385-2358

2a Gody Style: Straight shape, external coupling w/backshell Overall Length: 1.212 inches Overall Width: 0.812 inches Duthreaded Mounting Hole Diameter: 0.125 inches Center To Center Distance Between Mounting Facilities Parallel To Height: 0.125 inches Distance From Mounting Shoulder To Front Face: 0.427 inches Distance From Mounting Shoulder To Front Face: 0.428 Distance From Mounting Shoulder To Front Face: 0.428 Distance From Mounting Shoulder To Front Face: 0.429 Distance From Mounting Shou	Thread Class:
Straight shape, external coupling w/backshell Overall Length: 1.212 inches Overall Width: 0.812 inches Unthreaded Mounting Hole Diameter: 0.125 inches Center To Center Distance Between Mounting Facilities Parallel To Height: 0.594 inches Distance From Mounting Shoulder To Front Face: 0.427 inches Distance From Mounting Shoulder To Front Face: 0.427 inches Threaded Device Type: Back shell Thready Qty Per Inch (tpi): 28 Supplementary Features: Mounting method - flange Thread Series Designator: Unef Shelf Life: N/a Unef Shelf Life: N/a	2a
Straight shape, external coupling w/backshell Overall Length: 1.212 inches Overall Width: 0.812 inches Unthreaded Mounting Hole Diameter: 0.125 inches Center To Center Distance Between Mounting Facilities Parallel To Height: 0.594 inches Distance From Mounting Shoulder To Front Face: 0.427 inches Distance From Mounting Shoulder To Front Face: 0.427 inches Threaded Device Type: Back shell Thready Qty Per Inch (tpi): 28 Supplementary Features: Mounting method - flange Thread Series Designator: Unef Shelf Life: N/a Unef Shelf Life: N/a	Body Style:
Overall Length:1.212 inchesOverall Width:0.812 inchesUnthreaded Mounting Hole Diameter:0.125 inchesCenter To Center Distance Between Mounting Facilities Parallel To Height:0.594 inchesDistance From Mounting Shoulder To Front Face:0.427 inchesThreaded Device Type:Back shellThready Qty Per Inch (tpi):28Supplementary Features:Mounting method - flangeThread Series Designator:UnefShelf Life:N/aUnit of Measure:Pemilitarization:NoFig:	
Overall Width:0.812 inchesUnthreaded Mounting Hole Diameter:0.125 inchesCenter To Center Distance Between Mounting Facilities Parallel To Height:0.594 inchesDistance From Mounting Shoulder To Front Face:0.427 inchesThreaded Device Type:Back shellThready Qty Per Inch (tpi):28Supplementary Features:Mounting method - flangeThread Series Designator:UnefShelf Life:N/aInt Of Measure:Pemilitarization:NoFig:	Overall Length:
0.812 inches Unthreaded Mounting Hole Diameter: 0.125 inches Center To Center Distance Between Mounting Facilities Parallel To Height: 0.594 inches Distance From Mounting Shoulder To Front Face: 0.427 inches Threaded Device Type: Back shell Thready Qty Per Inch (tpi): 28 Supplementary Features: Mounting method - flange Thread Series Designator: Unef Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	1.212 inches
Untreaded Mounting Hole Diameter: 0.125 inches Center To Center Distance Between Mounting Facilities Parallel To Height: 0.594 inches Distance From Mounting Shoulder To Front Face: 0.427 inches Threaded Device Type: Back shell Thready Qty Per Inch (tpi): 28 Supplementary Features: Mounting method - flange Thread Series Designator: Unef Shelf Life: N/a Unit Of Measure: Demilitarization: No	Overall Width:
0.125 inches Center To Center Distance Between Mounting Facilities Parallel To Height: 0.594 inches Distance From Mounting Shoulder To Front Face: 0.427 inches Threaded Device Type: Back shell Thready Qty Per Inch (tpi): 28 Supplementary Features: Mounting method - flange Thread Series Designator: Unef Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	0.812 inches
Center To Center Distance Between Mounting Facilities Parallel To Height:0.594 inchesDistance From Mounting Shoulder To Front Face:0.427 inchesThreaded Device Type:Back shellThready Qty Per Inch (tpi):28Supplementary Features:Mounting method - flangeThread Series Designator:UnefShelf Life:N/aUnit Of Measure:-Demilitarization:NoFiig:	Unthreaded Mounting Hole Diameter:
0.594 inches Distance From Mounting Shoulder To Front Face: 0.427 inches Threaded Device Type: Back shell Thready Qty Per Inch (tpi): 28 Supplementary Features: Mounting method - flange Thread Series Designator: Unef Shelf Life: N/a Unit Of Measure: Demilitarization: No	0.125 inches
Distance From Mounting Shoulder To Front Face:0.427 inches0.427 inchesThreaded Device Type:Back shellThready Qty Per Inch (tpi):28Supplementary Features:Mounting method - flangeThread Series Designator:UnefShelf Life:N/aUnit Of Measure:Demilitarization:NoFig:	Center To Center Distance Between Mounting Facilities Parallel To Height:
0.427 inches Threaded Device Type: Back shell Thready Qty Per Inch (tpi): 28 Supplementary Features: Mounting method - flange Thread Series Designator: Unef Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	0.594 inches
Threaded Device Type:Back shellThready Qty Per Inch (tpi):28Supplementary Features:Mounting method - flangeThread Series Designator:UnefShelf Life:N/aUnit Of Measure:Demilitarization:NoFig:	Distance From Mounting Shoulder To Front Face:
Back shell Thready Qty Per Inch (tpi): 28 Supplementary Features: Mounting method - flange Thread Series Designator: Unef Shelf Life: N/a Unit Of Measure: Pomilitarization: No Fig:	0.427 inches
Thready Qty Per Inch (tpi): 28 Supplementary Features: Mounting method - flange Thread Series Designator: Unef Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Threaded Device Type:
28 Supplementary Features: Mounting method - flange Thread Series Designator: Unef Shelf Life: N/a Unit Of Measure: Fig:	Back shell
Supplementary Features: Mounting method - flange Thread Series Designator: Unef Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Thready Qty Per Inch (tpi):
Mounting method - flange Thread Series Designator: Unef Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	28
Thread Series Designator: Unef Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Supplementary Features:
Unef Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Mounting method - flange
Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Thread Series Designator:
N/a Unit Of Measure: Demilitarization: No Fiig:	Unef
Unit Of Measure: Demilitarization: No Fiig:	Shelf Life:
 Demilitarization: No Fiig:	N/a
Demilitarization: No Fiig:	Unit Of Measure:
No Fiig:	
Fiig:	Demilitarization:
	No
A039b0	Fiig:
	A039b0