

View Online at <https://aerobasegroup.com/nsn/5935-01-385-2917>

**Body Style:**

Hood, top opening w/clamp

**Overall Length:**

2.190 inches

**Overall Width:**

0.660 inches

**Cable Entrance Diameter:**

Between 0.110 inches and 0.275 inches

**Threaded Device Type:**

Coupling facility

**Mating End Quantity:**

1

**Contact Position Arrangement Style:**

25 single mating end

**Contact Removability:**

Removable single mating end single contact grouping

**Contact Maximum Current Rating In Amps:**

7.5 single mating end single contact grouping

**Polarization Method:**

Mating end

**Shell Type:**

Hood, top opening

**Connector Locking Method:**

Jackscrew

**Connector Cable Strain Relief Method:**

Cable clamp

**Terminal Location:**

Back single mating end single contact grouping

**Contact Material:**

Copper alloy single mating end single contact grouping

**Contact Surface Treatment:**

Gold single mating end single contact grouping and copper single mating end single contact grouping or gold single mating end single contact grouping and nickel single mating end single contact grouping

**Insert Material:**

Glass fiber single mating end and plastic single mating end

**Terminal Type:**

Crimp single mating end single contact grouping

**Shell Material:**

Plastic

**Insert Material Specification:**

Mil-m-14, ty sdg-f military specification all material responses single mating end

**Included Contact Quantity:**

25 single mating end single contact grouping

**Included Contact Type:**

Round socket single mating end single contact grouping

**Precious Material And Location:**

Contact surfaces gold

**Precious Material And Weight:**

0.025 gold grains, troy

**Precious Material:**

Gold

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A039b0

**Mil-std (military Standard):**

Mil-m-14 spec.