

View Online at <https://aerobasegroup.com/nsn/5935-01-385-3279>

Body Style:

Rectangular shape

Overall Length:

1.541 inches

Overall Height:

0.654 inches

Overall Width:

0.479 inches

Unthreaded Mounting Hole Diameter:

Between 0.115 inches and 0.125 inches

Distance Between Mounting Facility Centers:

Between 1.307 inches and 1.317 inches

Mating End Quantity:

15

Contact Position Arrangement Style:

15 single mating end

Contact Removability:

Removable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

7.5 single mating end single contact grouping

Contact Maximum Ac Voltage Rating In Volts:

300.0 single mating end single contact grouping

Polarization Method:

Guide pin/socket

Shell Type:

Solid

Connector Locking Method:

Friction

Radio Frequency Type Contact Characteristic Impedance In Ohms:

0.005 single mating end single contact grouping

Operating Temperature Rating:

Between -65.0 degrees celsius and 15.0 degrees celsius

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping and copper single mating end single contact grouping

Terminal Type:

Pin single mating end single contact grouping

Shell Material:

Zinc

Shell Surface Treatment:

Dichromate

Insert Material Specification:

Mil-m-14, sdg-f, ul 94v-0, green color military specification single material response single mating end

Unable To Decode:

Unable to decode and unable to decode

Included Contact Quantity:

15 single mating end single contact grouping

Included Contact Type:

Round pin single mating end single contact grouping

Precious Material And Location:

Internal surfaces gold

Precious Material:

Gold

Supplementary Features:

Mounting method - unthreaded hole

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-m-14 spec.