## NSN 5935-01-385-3313

Body Style: Straight shape Overall Length: 1.480 inches Overall Height: 0.655 inches Overall Width:

**Insert Material Specification:** 

6 slot

**Shell Guide Type And Location Designator:** 

Mil-m-24519, ty gsp-15f military specification 1st material response single mating end

Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-385-3313

| 0.282 inches                                                                                                                               |
|--------------------------------------------------------------------------------------------------------------------------------------------|
| Environmental Protection:                                                                                                                  |
| Corrosion resistant and fungus resistant and humidity resistant and shock resistant and vibration proof                                    |
| Mating End Quantity:                                                                                                                       |
| 1                                                                                                                                          |
| Contact Position Arrangement Style:                                                                                                        |
| 2 rows of contacts non-inserted board single mating end                                                                                    |
| Contact Removability:                                                                                                                      |
| Nonremovable single mating end single contact grouping                                                                                     |
| Contact Maximum Current Rating In Amps:                                                                                                    |
| 1.0 single mating end single contact grouping                                                                                              |
| Contact Maximum Ac Voltage Rating In Volts:                                                                                                |
| 500.0 single mating end single contact grouping                                                                                            |
| Polarization Method:                                                                                                                       |
| Shell                                                                                                                                      |
| Connector Locking Method:                                                                                                                  |
| Friction                                                                                                                                   |
| Terminal Location:                                                                                                                         |
| Back single mating end single contact grouping                                                                                             |
| Contact Material:                                                                                                                          |
| Copper alloy single mating end single contact grouping                                                                                     |
| Contact Surface Treatment:                                                                                                                 |
| Gold single mating end single contact grouping                                                                                             |
| Insert Material:                                                                                                                           |
| Plastic polyester single mating end and glass fiber single mating end                                                                      |
| Contact Surface Treatment Specification:                                                                                                   |
| Mil-g-45204, type 2, gr c, cl 1 military specification single treatment response single mating end single contact grouping                 |
| Terminal Type:                                                                                                                             |
| Wire lead single mating end single contact grouping                                                                                        |
| Contact Material Specification:                                                                                                            |
| Qq-c-530 federal specification single material response single mating end single contact grouping or qq-b-750 federal specification single |
| material response single mating end single contact grouping or qq-c-533 federal specification single material response single mating end   |
| single contact grouping                                                                                                                    |

## NSN 5935-01-385-3313

Electrical Plug Connector - Page 2 of 2



| Included Contact Quantity:                              |
|---------------------------------------------------------|
| 26 single mating end single contact grouping            |
| Included Contact Type:                                  |
| Square socket single mating end single contact grouping |
| Precious Material And Location:                         |
| Contact surfaces gold                                   |
| Precious Material And Weight:                           |
| 0.026 gold grains, troy                                 |
| Precious Material:                                      |
| Gold                                                    |
| Shelf Life:                                             |
| N/a                                                     |
| Unit Of Measure:                                        |
|                                                         |
| Demilitarization:                                       |
| No                                                      |
| Fiig:                                                   |

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.