NSN 5935-01-385-8336

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-385-8336

Body Style:

Straight shape, flush mount

Overall Length:

1.634 inches

Overall Height:

Between 3.060 inches and 3.090 inches

Overall Width:

Between 1.985 inches and 2.015 inches

Environmental Protection:

Humidity resistant and salt water resistant and shock resistant and thermal shock resistant and vibration resistant

Unthreaded Mounting Hole Diameter:

Between 0.118 inches and 0.122 inches

Center To Center Distance Between Mounting Facilities Parallel To Height:

2.783 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

1.437 inches

Distance From Mounting Shoulder To Front Face:

1.436 inches

Mating End Quantity:

Contact Position Arrangement Style:

67 2nd mating end

Contact Removability:

Removable all mating ends all contact groupings

Polarization Method:

3 polarization posts

Shell Type:

Solid

Connector Locking Method:

Friction

Terminal Location:

Back single mating end all contact groupings

Contact Material:

Copper alloy all mating ends all contact groupings

Contact Surface Treatment:

Gold 2nd mating end 1st contact grouping

Insert Material:

Plastic diallyl phthalate glass filled all mating ends or plastic epoxy all mating ends or plastic phenolic all mating ends

Contact Surface Treatment Specification:

Mil-g-45204, type 2, gr c, cl 1 military specification single treatment response 2nd mating end 1st contact grouping

Terminal Type:

Crimp single mating end all contact groupings

NSN 5935-01-385-8336

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.

Electrical Receptacle Connector - Page 2 of 2



Shell Material:
Aluminum alloy
Shell Surface Treatment:
Cadmium and chromate
Shell Surface Treatment Specification:
Qq-p-416, type 2 federal specification single treatment response
Shell Material Specification:
Qq-a-591 federal specification single material response or qq-a-367 federal specification single material response or qq-a-250 federal
specification single material response
Insert Material Specification:
Mil-m-14, ty gdi-30f or sdg-f federal specification 3rd material response all mating ends or called chemical 1288 bx mfr ref single material
response all mating ends or mil-m-14 military specification 3rd material response all mating ends
Unable To Decode:
Unable to decode and unable to decode and unable to decode
Included Contact Quantity:
64 2nd mating end 1st contact grouping
Included Contact Type:
Round pin all mating ends all contact groupings
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.094 gold grains, troy
Precious Material:
Gold
Test Data Document:
81349-mil-c-81659 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Specification Data:
81349-mil-c-81659/35 government specification
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:
No
Fiig: