

View Online at <https://aerobasegroup.com/nsn/5935-01-386-3599>

Overall Length:

Between 1.410 inches and 1.430 inches

Overall Diameter:

1.167 inches

Environmental Protection:

Shock resistant and vibration resistant and pressure proof and thermal shock resistant and moisture resistant and corrosion resistant and dust resistant and sand resistant and fungus resistant

Unthreaded Mounting Hole Diameter:

Between 0.125 inches and 0.126 inches

Threaded Device Type:

Coupling facility

Mating End Quantity:

2

Contact Position Arrangement Style:

Nonstd all mating ends

Contact Removability:

Nonremovable all mating ends single contact grouping

Contact Maximum Ac Voltage Rating In Volts:

335.0 all mating ends single contact grouping

Contact Maximum Frequency Rating:

18.0 gigahertz all mating ends single contact grouping

Polarization Method:

Keyway or multiple keyway

Insert Position In Deg:

102.0

Shell Type:

Solid

Connector Locking Method:

Externally threaded shell

Radio Frequency Type Contact Characteristic Impedance In Ohms:

50.0 all mating ends single contact grouping

Operating Temperature Rating:

Between -65.0 degrees celsius and 125.0 degrees celsius

Included Contact Quantity:

1 all mating ends single contact grouping

Bushing Accommodation Hole Shape:

Round w/flat

Included Contact Type:

Coaxial socket all mating ends single contact grouping

Specification Data:

99971-295a6564 manufacturers source control

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0