

View Online at <https://aerobasegroup.com/nsn/5935-01-386-3613>

**Overall Length:**

Between 1.410 inches and 1.430 inches

**Overall Diameter:**

1.167 inches

**Environmental Protection:**

Shock resistant and thermal shock resistant and moisture resistant and corrosion resistant and dust resistant and sand resistant and fungus resistant

**Unthreaded Mounting Hole Diameter:**

Between 0.125 inches and 0.126 inches

**Threaded Device Type:**

Coupling facility

**Mating End Quantity:**

2

**Contact Position Arrangement Style:**

Nonstd all mating ends

**Contact Removability:**

Nonremovable all mating ends single contact grouping

**Contact Maximum Ac Voltage Rating In Volts:**

335.0 all mating ends single contact grouping

**Contact Maximum Frequency Rating:**

18.0 gigahertz all mating ends single contact grouping

**Polarization Method:**

Keyway or multiple keyway

**Insert Position In Deg:**

114.0

**Shell Type:**

Solid

**Connector Locking Method:**

Externally threaded shell

**Radio Frequency Type Contact Characteristic Impedance In Ohms:**

50.0 all mating ends single contact grouping

**Operating Temperature Rating:**

Between -65.0 degrees celsius and 125.0 degrees celsius

**Included Contact Quantity:**

1 all mating ends single contact grouping

**Bushing Accommodation Hole Shape:**

Round w/flat

**Included Contact Type:**

Coaxial socket all mating ends single contact grouping

**Specification Data:**

99971-295a6564 manufacturers source control

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A039b0