NSN 5935-01-386-7175

Connector Adapter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-386-7175

Overal	llen	ath.
Overai	IFCI	ıuıı.

Between 1.410 inches and 1.430 inches

Overall Diameter:

1.167 inches

Environmental Protection:

Corrosion resistant and dust resistant and fungus resistant and pressure proof and moisture resistant and sand resistant and shock resistant and thermal shock resistant and vibration resistant

Unthreaded Mounting Hole Diameter:

Between 0.125 inches and 0.126 inches

Mating End Quantity:

2

Contact Position Arrangement Style:

Nonstd all mating ends

Contact Removability:

Nonremovable all mating ends single contact grouping

Contact Maximum Ac Voltage Rating In Volts:

335.0 all mating ends single contact grouping

Contact Maximum Frequency Rating:

18.0 gigahertz all mating ends single contact grouping

Polarization Method:

Keyway or multiple keyway

Insert Position In Deg:

90.0

Shell Type:

Solid

Connector Locking Method:

Externally threaded shell

Radio Frequency Type Contact Characteristic Impedance In Ohms:

50.0 all mating ends single contact grouping

Operating Tempurature Rating:

Between -65.0 degrees celsius and 125.0 degrees celsius

Included Contact Quantity:

1 all mating ends single contact grouping

Bushing Accommodation Hole Shape:

Round w/flat

Included Contact Type:

Coaxial socket all mating ends single contact grouping

Specification Data:

99971-295a6564 manufacturers source control

Shelf Life:

N/a

Unit Of Measure:

--

NSN 5935-01-386-7175

Connector Adapter - Page 2 of 2



Demilitarization:

No

Fiig:

A039b0