NSN 5935-01-386-9502

Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-386-9502
Thread Class:
2a
Thread Direction:
Right-hand
Body Style:
Straight shape, internal coupling
Overall Length:
1.234 inches
Overall Diameter:
1.891 inches
Environmental Protection:
Moisture proof and salt water resistant and vibration proof and corrosion resistant and dust resistant and fuel resistant and fungus resistant
and humidity resistant and oil resistant and shock resistant and thermal shock resistant and vibration resistant
Threaded Device Type:
Coupling facility
Mating End Quantity:
1
Contact Position Arrangement Style:
25-29 single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Polarization Method:
Key, multiple key groove
Insert Position In Deg:
26.0 and 100.0 and 128.0 and 228.0 and 265.0
Shell Type:
Solid
Connector Locking Method:
Shell twistlock and internally threaded coupling ring and bayonet slot
Thread Length:
18.0 millimeters
Thread Size:
1.438 inches
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping
Insert Material:

Contact Surface Treatment Specification: Mil-g-45204 military specification single treatment response single mating end single contact grouping

Plastic epoxy single mating end

NSN 5935-01-386-9502Electrical Plug Connector - Page 2 of 2



Terminal Type:
Crimp single mating end single contact grouping
Shell Material:
Aluminum alloy
Shell Surface Treatment:
Cadmium and chromate and nickel
Shell Surface Treatment Specification:
Qq-p-416, type 2 federal specification 1st treatment response and qq-p-416, ty2 federal specification 2nd treatment response
Included Contact Quantity:
29 single mating end single contact grouping
Included Contact Type:
Round pin single mating end single contact grouping
Precious Material And Location:
Contact finish gold
Precious Material:
Gold
Thread Series Designator:
Unef
Specification Data:
96906-mil-c-38999 government standard
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0
Mil-std (military Standard):
Mil-g-45204 spec.