## NSN 5935-01-387-7916

Thread Class: 2a and 2b

Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-387-7916

Thread Direction:
Right-hand and right-hand
Body Style:
Straight shape, internal coupling
Overall Length:
1.370 inches
Overall Diameter:
1.098 inches
Environmental Protection:
Humidity resistant and salt water resistant and shock proof and vibration proof
Threaded Device Type:
Back shell and coupling facility
Mating End Quantity:
1
Contact Position Arrangement Style:
3-dec single mating end
Contact Removability:
Removable single mating end single contact grouping
Polarization Method:
Keyway or multiple keyway
Insert Position In Deg:
0.0
0.0
Shell Type:
Shell Type:
Shell Type: Solid
Shell Type: Solid Connector Locking Method:
Shell Type: Solid Connector Locking Method: Internally threaded coupling ring
Shell Type: Solid Connector Locking Method: Internally threaded coupling ring Thread Size:
Shell Type: Solid Connector Locking Method: Internally threaded coupling ring Thread Size: 0.750 inches and 0.875 inches
Shell Type: Solid Connector Locking Method: Internally threaded coupling ring Thread Size: 0.750 inches and 0.875 inches Terminal Location:
Shell Type: Solid Connector Locking Method: Internally threaded coupling ring Thread Size: 0.750 inches and 0.875 inches Terminal Location: Back single mating end single contact grouping
Shell Type: Solid Connector Locking Method: Internally threaded coupling ring Thread Size: 0.750 inches and 0.875 inches Terminal Location: Back single mating end single contact grouping Contact Material:
Shell Type: Solid Connector Locking Method: Internally threaded coupling ring Thread Size: 0.750 inches and 0.875 inches Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping
Shell Type: Solid Connector Locking Method: Internally threaded coupling ring Thread Size: 0.750 inches and 0.875 inches Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Contact Surface Treatment:
Shell Type: Solid Connector Locking Method: Internally threaded coupling ring Thread Size: 0.750 inches and 0.875 inches Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Contact Surface Treatment: Gold single mating end single contact grouping
Shell Type: Solid Connector Locking Method: Internally threaded coupling ring Thread Size: 0.750 inches and 0.875 inches Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Contact Surface Treatment: Gold single mating end single contact grouping Insert Material:
Shell Type: Solid Connector Locking Method: Internally threaded coupling ring Thread Size: 0.750 inches and 0.875 inches Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Contact Surface Treatment: Gold single mating end single contact grouping Insert Material: Plastic epoxy single mating end
Shell Type: Solid  Connector Locking Method: Internally threaded coupling ring Thread Size: 0.750 inches and 0.875 inches Terminal Location: Back single mating end single contact grouping  Contact Material: Copper alloy single mating end single contact grouping  Contact Surface Treatment: Gold single mating end single contact grouping  Insert Material: Plastic epoxy single mating end Terminal Type:

## **NSN 5935-01-387-7916**Electrical Plug Connector - Page 2 of 2



Shell Surface Treatment:
Cadmium
ncluded Contact Quantity:
3 single mating end single contact grouping
ncluded Contact Type:
Round pin single mating end single contact grouping
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.003 gold grains, troy
Precious Material:
Gold
Test Data Document:
31349-mil-c-83723 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Thread Series Designator:
Jnef and unef
Specification Data:
31349-mil-c-83723/96 government specification
Shelf Life:
N/a
Unit Of Measure:
-
Demilitarization:
No
Filg:
4039b0