

View Online at <https://aerobasegroup.com/nsn/5935-01-387-7951>

Thread Direction:

Right-hand

Body Style:

Straight shape, external coupling

Overall Length:

31.5 millimeters

Overall Height:

Between 28.3 millimeters and 28.9 millimeters

Overall Width:

Between 28.3 millimeters and 28.9 millimeters

Unable To Decode:

Unable to decode and unable to decode

Unable To Decode:

Unable to decode and unable to decode

Environmental Protection:

Moisture proof and salt water resistant and vibration proof and corrosion resistant and dust resistant and fuel resistant and fungus resistant and humidity resistant and oil resistant and shock resistant and thermal shock resistant and vibration resistant

Center To Center Distance Between Mounting Facilities Parallel To Height:

21.815 millimeters

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

21.815 millimeters

Distance From Mounting Shoulder To Front Face:

Between 19.5 millimeters and 20.9 millimeters

Threaded Device Type:

Back shell and coupling facility

Mating End Quantity:

1

Contact Position Arrangement Style:

13-08 single mating end

Contact Removability:

Removable single mating end single contact grouping

Polarization Method:

Keyway or multiple keyway

Insert Position In Deg:

113.0 and 156.0 and 182.0 and 292.0

Shell Type:

Solid

Connector Locking Method:

Externally threaded shell

Operating Temperature Rating:

Between -65.0 degrees celsius and 200.0 degrees celsius

Thread Size:

18.0 millimeters

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping

Insert Material:

Plastic epoxy single mating end

Contact Surface Treatment Specification:

Mil-g-45204 military specification single treatment response single mating end single contact grouping

Terminal Type:

Crimp single mating end single contact grouping

Shell Material:

Aluminum alloy

Shell Surface Treatment:

Cadmium

Shell Surface Treatment Specification:

Qq-p-416 federal specification single treatment response

Thread Tolerance Class:

6h external

Included Contact Quantity:

8 single mating end single contact grouping

Included Contact Type:

Round socket single mating end single contact grouping

Precious Material And Location:

Contact finish gold

Precious Material:

Gold

Supplementary Features:

Mounting method - flange

Thread Series Designator:

Iso m

Specification Data:

81349-mil-c-38999 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.