

View Online at <https://aerobasegroup.com/nsn/5935-01-388-0113>

Body Style:

Straight shape, internal coupling

Overall Length:

Between 1.0006 inches and 1.0306 inches

Overall Diameter:

0.600 inches

Mating End Quantity:

2

Contact Position Arrangement Style:

Nonstd single mating end

Contact Removability:

Nonremovable single mating end single contact grouping

Contact Maximum Ac Voltage Rating In Volts:

500.0 all mating ends all contact groupings

Contact Maximum Frequency Rating:

1.0 gigahertz all mating ends all contact groupings

Polarization Method:

Guide pin/socket

Shell Type:

Solid

Connector Locking Method:

Shell twistlock

Radio Frequency Type Contact Characteristic Impedance In Ohms:

50.0 all mating ends all contact groupings

Operating Temperature Rating:

Between -65.0 degrees celsius and 165.0 degrees celsius

Contact Material:

Beryllium single mating end single contact grouping and copper single mating end single contact grouping

Contact Surface Treatment:

Silver single mating end single contact grouping

Contact Material Specification:

Qq-c-530 federal specification single material response single mating end single contact grouping

Shell Material:

Copper alloy

Shell Surface Treatment:

Nickel

Shell Material Specification:

Qq-b-626, comp 22, 1/2 hard with 0.0002 - 0.0003 silver plate. Federal specification single material response

Unable To Decode:

Unable to decode and unable to decode

Included Contact Quantity:

1 single mating end single contact grouping

Included Contact Type:

Coaxial pin all mating ends single contact grouping

Precious Material And Location:

Contact surfaces silver

Precious Material:

Silver

Specification Data:

26916-010-007083 professional/industrial association specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A039b0