NSN 5935-01-388-5534



Electrical Receptacle Connector - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5935-01-388-5534 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Straight shape, external coupling **Overall Length:** 1.133 inches **Overall Height:** 1.812 inches **Overall Width:** 1.812 inches Center To Center Distance Between Mounting Facilities Parallel To Height: 1.500 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 1.500 inches **Distance From Mounting Shoulder To Front Face:** 0.602 inches **Threaded Device Type:** Back shell **Mating End Quantity:** 1 **Contact Position Arrangement Style:** 25-43 single mating end **Contact Removability:** Removable single mating end all contact groupings Shell Type: Solid **Connector Locking Method:** Bayonet pin **Thread Size:** 1.133 inches **Terminal Location:** Back single mating end all contact groupings **Contact Material:** Copper alloy single mating end all contact groupings

Contact Surface Treatment:

Gold single mating end all contact groupings

Insert Material:

Plastic epoxy single mating end

Terminal Type:

Crimp single mating end all contact groupings

NSN 5935-01-388-5534

Electrical Receptacle Connector - Page 2 of 2



Shell Material:
Aluminum alloy
Shell Surface Treatment:
Passivate
Included Contact Quantity:
23 single mating end 2nd contact grouping
Included Contact Type:
Round pin single mating end all contact groupings
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.043 gold grains, troy
Precious Material:
Gold
Test Data Document:
96906-ms27466e25a43p standard (includes industry or association standards, individual manufactureer standards, etc.).
Thread Series Designator:
Unef
Specification Data:
81349-mil-c-38999 government standard
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0
Mil-std (military Standard):
Mil-c-38999 spec.