NSN 5935-01-388-5918

Body Style:

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-388-5918

Straight shape
Overall Length:
3.955 inches
Overall Height:
0.460 inches
Overall Width:
0.250 inches
Unthreaded Mounting Hole Diameter:
Between 0.091 inches and 0.098 inches
Mating End Quantity:
1
Contact Position Arrangement Style:
2 rows of contacts non-inserted board single mating end
Contact Removability:
Removable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
3.0 single mating end single contact grouping
Polarization Method:
Mating end
Shell Type:
0-1:4
Solid
Connector Locking Method:
Connector Locking Method:
Connector Locking Method: Friction
Connector Locking Method: Friction Terminal Location:
Connector Locking Method: Friction Terminal Location: Back single mating end single contact grouping
Connector Locking Method: Friction Terminal Location: Back single mating end single contact grouping Contact Material:
Connector Locking Method: Friction Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping
Connector Locking Method: Friction Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Insert Material:
Connector Locking Method: Friction Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Insert Material: Plastic diallyl phthalate single mating end
Connector Locking Method: Friction Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Insert Material: Plastic diallyl phthalate single mating end Terminal Type:
Connector Locking Method: Friction Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Insert Material: Plastic diallyl phthalate single mating end Terminal Type: Printed circuit single mating end single contact grouping
Connector Locking Method: Friction Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Insert Material: Plastic diallyl phthalate single mating end Terminal Type: Printed circuit single mating end single contact grouping Shell Material:
Connector Locking Method: Friction Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Insert Material: Plastic diallyl phthalate single mating end Terminal Type: Printed circuit single mating end single contact grouping Shell Material: Aluminum alloy
Connector Locking Method: Friction Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Insert Material: Plastic diallyl phthalate single mating end Terminal Type: Printed circuit single mating end single contact grouping Shell Material: Aluminum alloy Shell Surface Treatment:
Connector Locking Method: Friction Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Insert Material: Plastic diallyl phthalate single mating end Terminal Type: Printed circuit single mating end single contact grouping Shell Material: Aluminum alloy Shell Surface Treatment: Nickel
Connector Locking Method: Friction Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Insert Material: Plastic diallyl phthalate single mating end Terminal Type: Printed circuit single mating end single contact grouping Shell Material: Aluminum alloy Shell Surface Treatment: Nickel Included Contact Quantity:
Connector Locking Method: Friction Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Insert Material: Plastic diallyl phthalate single mating end Terminal Type: Printed circuit single mating end single contact grouping Shell Material: Aluminum alloy Shell Surface Treatment: Nickel Included Contact Quantity: 128 single mating end single contact grouping
Connector Locking Method: Friction Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Insert Material: Plastic diallyl phthalate single mating end Terminal Type: Printed circuit single mating end single contact grouping Shell Material: Aluminum alloy Shell Surface Treatment: Nickel Included Contact Quantity: 128 single mating end single contact grouping Included Contact Type:

NSN 5935-01-388-5918

Electrical Receptacle Connector - Page 2 of 2



	1	:.	~	84				
ι	JN	IT	UΤ	IVI	ea	Sι	ire:	•

--

Demilitarization:

No

Fiig:

A039b0