NSN 5935-01-388-6373



Electrical Receptacle Connector - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5935-01-388-6373 **Thread Class:** 2b **Thread Direction:** Right-hand **Body Style:** Straight shape, flush mount **Overall Length:** 1.634 inches **Overall Height:** 3.090 inches **Overall Width:** 2.015 inches Center To Center Distance Between Mounting Facilities Parallel To Height: 2.782 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 1.436 inches **Distance From Mounting Shoulder To Front Face:** 0.065 inches **Threaded Device Type:** Mounting hole **Mating End Quantity:** 2 **Contact Position Arrangement Style:** 26 1st mating end **Contact Removability:** Removable all mating ends all contact groupings Shell Type: Solid **Connector Locking Method:** Friction **Thread Size:** 0.112 inches **Terminal Location:** Back all mating ends all contact groupings **Contact Material:** Copper alloy all mating ends all contact groupings **Contact Surface Treatment:** Gold all mating ends all contact groupings

Insert Material:

Plastic diallyl phthalate all mating ends and glass fiber all mating ends or plastic epoxy all mating ends and plastic phenolic all mating ends

Terminal Type:

Crimp all mating ends all contact groupings

NSN 5935-01-388-6373

Electrical Receptacle Connector - Page 2 of 2



Shell Material:
Aluminum alloy
Shell Surface Treatment:
Cadmium and chromate
Included Contact Quantity:
26 1st mating end 1st contact grouping
Included Contact Type:
Round socket 1st mating end 2nd contact grouping
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.132 gold grains, troy
Precious Material:
Gold
Test Data Document:
8134981659/35a20059 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in
specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data or
certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Thread Series Designator:
Unc
Specification Data:
81349-mil-c-81659/35 government specification
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0