NSN 5935-01-388-6843

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-388-6843

Body Style: Straight shape **Overall Length:** Between 5.840 inches and 5.860 inches **Overall Height:** 0.700 inches **Overall Width:** 0.250 inches **Environmental Protection:** Moisture resistant **Unthreaded Mounting Hole Diameter:** 0.008 inches **Mating End Quantity: Contact Position Arrangement Style:** 2 rows of contacts non-inserted board single mating end **Contact Removability:** Nonremovable single mating end single contact grouping **Polarization Method:** Guide pin/socket **Connector Locking Method:** Friction **Terminal Location:** Back single mating end single contact grouping **Contact Material:** Copper alloy single mating end single contact grouping **Contact Surface Treatment:** Gold single mating end single contact grouping and nickel single mating end single contact grouping **Insert Material:** Plastic polyphenylene single mating end **Contact Surface Treatment Specification:** Mil-g-45204, type 2, cl 00 military specification 1st treatment response single mating end single contact grouping and qq-n-290 federal specification 2nd treatment response single mating end single contact grouping **Terminal Type:** Pin single mating end single contact grouping **Contact Material Specification:**

Mil-c-55302 military specification single material response single mating end single contact grouping

Insert Material Specification:

Mil-c-55302 military specification single material response single mating end

Unable To Decode:

Unable to decode and unable to decode

Included Contact Quantity:

90 single mating end single contact grouping

NSN 5935-01-388-6843

Electrical Receptacle Connector - Page 2 of 2



Included Contact Type

Round socket single mating end single contact grouping

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.090 gold grains, troy

Precious Material:

Gold

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A039b0

Mil-std (military Standard):

Mil-c-55302 spec.