## NSN 5935-01-388-7347

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-388-7347 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Straight shape, external coupling **Overall Length:** Between 1.327 inches and 1.347 inches **Overall Height:** Between 1.695 inches and 1.711 inches **Overall Width:** Between 1.695 inches and 1.711 inches **Unthreaded Mounting Hole Diameter:** Between 0.143 inches and 0.153 inches Center To Center Distance Between Mounting Facilities Parallel To Height: Between 1.370 inches and 1.380 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: Between 1.370 inches and 1.380 inches **Distance From Mounting Shoulder To Front Face:** Between 0.894 inches and 0.906 inches **Threaded Device Type:** Back shell **Mating End Quantity: Contact Position Arrangement Style:** 4 single mating end **Contact Removability:** Removable single mating end single contact grouping **Polarization Method:** Key or multiple key Shell Type: **Connector Locking Method:** Bayonet pin Thready Qty Per Inch (tpi): 28 **Thread Size:** 1.500 inches **Terminal Location:** 

Contact Material:

Copper alloy single mating end single contact grouping

Back single mating end single contact grouping

## NSN 5935-01-388-7347

Electrical Receptacle Connector - Page 2 of 2



Contact Surface Treatment:
Gold single mating end single contact grouping
Insert Material:
Rubber fluorosilicone class fq single mating end
Terminal Type:
Crimp single mating end single contact grouping
Shell Material:
Aluminum alloy
Shell Surface Treatment:
Nickel
Included Contact Quantity:
4 single mating end single contact grouping
Included Contact Type:
Round pin single mating end single contact grouping
Precious Material:
Gold
Thread Series Designator:
Un
Specification Data:
$81349 - 81511/41 wj 02 + 4\ professional/industrial\ association\ specification$
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0