NSN 5935-01-388-9183

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-388-9183

Body Style:
Straight shape
Overall Length:
3.850 inches
Overall Height:
0.715 inches
Overall Width:
0.250 inches
Environmental Protection:
Heat resistant and cold resistant and vibration resistant and corrosion resistant and shock resistant and humidity resistant
Unthreaded Mounting Hole Diameter:
0.120 inches
Distance Between Mounting Facility Centers:
3.600 inches
Mating End Quantity:
1
Contact Position Arrangement Style:
2 rows of contacts non-inserted board single mating end
Contact Removability:
Removable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
5.0 single mating end single contact grouping
Polarization Method:
Guide pin/socket
Connector Locking Method:
Friction
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping
Insert Material:
Plastic phenolic mineral filled single mating end
Contact Surface Treatment Specification

Mil-g-45204 military specification single treatment response single mating end single contact grouping

Terminal Type:

Crimp single mating end single contact grouping

Contact Material Specification:

Mil-c-55302 military specification single material response single mating end single contact grouping

Insert Material Specification:

Mil-m-14, ty mfh military specification single material response single mating end

NSN 5935-01-388-9183

Electrical Receptacle Connector - Page 2 of 2



Unable To Decode:
Unable to decode and unable to decode
Included Contact Quantity:
60 single mating end single contact grouping
Included Contact Type:
Round socket single mating end single contact grouping
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.060 gold grains, troy
Precious Material:
Gold
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A039b0

Mil-std (military Standard):

Mil-c-55302 spec.