NSN 5935-01-389-3057

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-389-3057 **Thread Class:** 2a and 2a **Thread Direction:** Right-hand and right-hand **Body Style:** Straight shape, external coupling w/backshell **Overall Length:** 2.437 inches **Overall Height:** 1.188 inches **Overall Width:** 1.188 inches **Unthreaded Mounting Hole Diameter:** 0.150 inches Center To Center Distance Between Mounting Facilities Parallel To Height: 0.906 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 0.906 inches **Distance From Mounting Shoulder To Front Face:** 0.562 inches **Threaded Device Type:** Back shell and coupling facility **Mating End Quantity: Contact Position Arrangement Style:** 14s-9 all mating ends **Contact Removability:** Removable single mating end single contact grouping **Polarization Method:** Key, multiple key groove **Insert Position In Deg:** 0.0 Shell Type: Solid **Connector Locking Method:** Externally threaded shell **Thread Size:**

0.750 inches and 0.875 inches

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

NSN 5935-01-389-3057

Electrical Receptacle Connector - Page 2 of 2



Contact Surface Treatment:
Gold single mating end single contact grouping
Terminal Type:
Crimp single mating end single contact grouping
Shell Material:
Aluminum alloy
Shell Surface Treatment:
Cadmium and chromate
Included Contact Quantity:
2 single mating end single contact grouping
Bushing Accommodation Hole Shape:
Round
Included Contact Type:
Round pin single mating end single contact grouping
Precious Material And Location:
Contact surfaces gold
Precious Material:
Gold
Thread Series Designator:
Unef and unef
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0